

MODEL		SUD-CAV-05/SUD-CAV-10		
<b>Cable Specification:</b>				
Component		Part A	Part B	Part C
Conductor	Constitution	7/0.11mm	S28/0.12mm	7/0.2mm
	Material	OFC	CCA 23%copper	CCA 23%copper
Insulation	Number of core wires	1C	/	2C
	Material	PE	/	PVC
	Nom. O.D. :mm	1.3±0.05	/	1.0±0.05
	Color	Transparent	/	Black/Red
Jacket	Nom. O.D. :mm	2.8+2.8±0.20		
	Material	PVC		
	Nom. thickness mm	0.40 Ref		
	Color	Black		
<b>Physical and Electrical Performance</b>				
MODEEL		SUD-CAV-05	SUD-CAV-10	
Connector	DC Power Port	Input:DC5521 Female Output:DC5521 Male Color: Red		
	Video Port	BNC Plug 75 Ohm Male-to-male Color: Yellow		
Video Spec.	Video Format	CVI/TVI/AHD/CVBS		
	Resolution	720P/920P/1080P/3MP/4MP/5MP/8MP		
Length "L"		5 meters	10 meters	
Rated voltage		DC 30V		
Insulation impedance		FPE/PVC-DC: 500V 100M Ohm MIN(20°C)		
High-Voltage Holding Test		AC-500V/1 SEC MIN		
Operating temperature		-10°C~60°C		
N. W.				
G. W.				
Size L*W*H mm				

**Diagram**

